


一体成型电感

产品尺寸 Product Size



单位 Unit: 毫米 (mm)

型号 Size	A	B	C	D	E	G	H	I
0412系列	4.20 ± 0.30	4.45 ± 0.50	1.20 Max	1.10 ± 0.50	2.00 ± 0.30	1.70 Ref	5.10 Ref	2.50 Ref
0415系列	4.20 ± 0.30	4.45 ± 0.50	1.50 Max	1.10 ± 0.50	2.00 ± 0.30	1.70 Ref	5.10 Ref	2.50 Ref
0420系列	4.20 ± 0.30	4.45 ± 0.50	2.00 Max	1.10 ± 0.50	2.00 ± 0.30	1.70 Ref	5.10 Ref	2.50 Ref
0515系列	5.20 ± 0.30	5.60 ± 0.50	1.50 Max	1.30 ± 0.50	2.20 ± 0.30	1.90 Ref	6.20 Ref	2.50 Ref
0518系列	5.20 ± 0.30	5.60 ± 0.50	1.80 Max	1.30 ± 0.50	2.20 ± 0.30	1.90 Ref	6.20 Ref	2.50 Ref
0520系列	5.20 ± 0.30	5.60 ± 0.50	2.00 Max	1.30 ± 0.50	2.20 ± 0.30	1.90 Ref	6.20 Ref	2.50 Ref
0530系列	5.20 ± 0.30	5.60 ± 0.50	3.00 Max	1.30 ± 0.50	2.20 ± 0.30	1.90 Ref	6.20 Ref	2.50 Ref
0540系列	5.20 ± 0.30	5.60 ± 0.50	4.00 Max	1.30 ± 0.50	2.20 ± 0.30	1.90 Ref	6.20 Ref	2.50 Ref
0615系列	6.60 ± 0.30	7.10 ± 0.50	1.50 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0618系列	6.60 ± 0.30	7.10 ± 0.50	1.80 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0620系列	6.60 ± 0.30	7.10 ± 0.50	2.00 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0624系列	6.60 ± 0.30	7.10 ± 0.50	2.40 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0630系列	6.60 ± 0.30	7.10 ± 0.50	3.00 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0640系列	6.60 ± 0.30	7.10 ± 0.50	4.00 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0650系列	6.60 ± 0.30	7.10 ± 0.50	5.00 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0658系列	6.60 ± 0.30	7.10 ± 0.50	5.80 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0660系列	6.60 ± 0.30	7.10 ± 0.50	6.00 Max	1.60 ± 0.50	3.00 ± 0.30	2.90 Ref	7.80 Ref	3.50 Ref
0820系列	8.00 ± 0.30	8.70 ± 0.50	2.00 Max	1.80 ± 0.50	3.00 ± 0.30	4.50 Ref	9.00 Ref	3.50 Ref
0830系列	8.00 ± 0.30	8.70 ± 0.50	3.00 Max	1.80 ± 0.50	3.00 ± 0.30	4.50 Ref	9.00 Ref	3.50 Ref
0840系列	8.00 ± 0.30	8.70 ± 0.50	4.00 Max	1.80 ± 0.50	3.00 ± 0.30	4.50 Ref	9.00 Ref	3.50 Ref
0850系列	8.00 ± 0.30	8.70 ± 0.50	5.00 Max	1.80 ± 0.50	3.00 ± 0.30	4.50 Ref	9.00 Ref	3.50 Ref
0860系列	8.00 ± 0.30	8.70 ± 0.50	6.00 Max	1.80 ± 0.50	3.00 ± 0.30	4.50 Ref	9.00 Ref	3.50 Ref
1020系列	10.20 ± 0.30	11.5 Max	2.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1024系列	10.20 ± 0.30	11.5 Max	2.40 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1025系列	10.20 ± 0.30	11.5 Max	2.50 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1030系列	10.20 ± 0.30	11.5 Max	3.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1040系列	10.20 ± 0.30	11.5 Max	4.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1045系列	10.20 ± 0.30	11.5 Max	4.50 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1050系列	10.20 ± 0.30	11.5 Max	5.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref

1060系列	10.20 ± 0.30	11.5 Max	6.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1075系列	10.20 ± 0.30	11.5 Max	7.50 Max	2.10 ± 0.50	3.00 ± 0.50	6.00 Ref	11.80 Ref	4.50 Ref
1080系列	10.20 ± 0.30	11.20 ± 0.50	8.00 Max	2.00 ± 0.50	3.00 ± 0.30	6.00 Ref	11.80 Ref	3.50 Ref
1175系列	7.0 ± 0.30	10.50 ± 0.50	5.00 Max	2.00 ± 0.50	2.80 ± 0.50	5.50 Ref	11.80 Ref	3.50 Ref
1230系列	12.80 ± 0.30	14.50 Max	3.00 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1235系列	12.80 ± 0.30	14.50 Max	3.50 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1240系列	12.80 ± 0.30	14.50 Max	4.00 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1250系列	12.80 ± 0.30	14.50 Max	5.00 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1260系列	12.80 ± 0.30	14.50 Max	6.00 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1265系列	12.80 ± 0.30	14.50 Max	6.50 Max	2.50 ± 0.50	3.80 ± 0.30	7.60 Ref	14.10 Ref	4.50 Ref
1770系列	17.00 ± 0.30	18.50Max	7.00 Max	2.50 ± 0.50	12.00 ± 0.30	11.2Ref	18.70Ref	12.80Ref

DH0412系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0412H-R22M	0.22	$\pm 20\%$	100	1000	9.5	11	7	8	10	11
DH0412H-R47M	0.47	$\pm 20\%$	100	1000	18	22	6	6.2	8	8.5
DH0412H-R60M	0.6	$\pm 20\%$	100	1000	25	30	5	5.2	7.5	8
DH0412H-R68M	0.68	$\pm 20\%$	100	1000	27	34	4.7	4.9	5.8	6
DH0412H-1R0M	1	$\pm 20\%$	100	1000	40	50	4.5	4.7	5.3	5.5
DH0412H-1R5M	1.5	$\pm 20\%$	100	1000	65	72	3.3	3.5	3.8	4
DH0412H-2R2M	2.2	$\pm 20\%$	100	1000	68	80	2.8	3	3.5	4
DH0412H-3R3M	3.3	$\pm 20\%$	100	1000	128	145	2	2.2	2.8	3
DH0412H-4R7M	4.7	$\pm 20\%$	100	1000	162	180	1.6	1.8	2.2	2.8

DH0415系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0415H-R22M	0.22	$\pm 20\%$	100	1000	9.5	11	7.0	8.0	10.0	11.0
DH0415H-1R0M	1	$\pm 20\%$	100	1000	38	46	4.8	5.0	6.8	7.0
DH0415H-1R5M	1.5	$\pm 20\%$	100	1000	42.5	52	4.3	4.5	5.0	5.5
DH0415H-2R2M	2.2	$\pm 20\%$	100	1000	67	78	3	3.2	4.3	4.5
DH0415H-3R3M	3.3	$\pm 20\%$	100	1000	95	110	2.3	2.5	3.0	3.5
DH0415H-4R7M	4.7	$\pm 20\%$	100	1000	123	140	2	2.2	2.8	3.0

DH0420系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0420H-R10N	0.10	$\pm 30\%$	100	1000	4.4	5.3	12.0	13.0	20.0	22.0
DH0420H-R22M	0.22	$\pm 20\%$	100	1000	5.3	6.4	10.0	12.0	13.0	14.0
DH0420H-R27M	0.27	$\pm 20\%$	100	1000	8.5	10.2	8.5	9.0	11.0	12.0
DH0420H-R33M	0.33	$\pm 20\%$	100	1000	8.5	10.2	8.5	9.0	11.0	12.0
DH0420H-R47M	0.47	$\pm 20\%$	100	1000	10.5	13.2	8.0	8.5	10.0	11.0
DH0420H-R56M	0.56	$\pm 20\%$	100	1000	16.5	20.0	6.5	7.0	9.0	10.0
DH0420H-R68M	0.68	$\pm 20\%$	100	1000	17.5	21.0	6.0	6.5	8.5	9.0
DH0420H-1R0M	1.0	$\pm 20\%$	100	1000	27.0	34.0	5.5	6.0	7.0	8.0
DH0420H-1R5M	1.5	$\pm 20\%$	100	1000	32.5	39.0	4.5	4.8	6.5	7.0
DH0420H-2R2M	2.2	$\pm 20\%$	100	1000	48.0	58.0	3.6	4.0	5.5	6.0
DH0420H-3R3M	3.3	$\pm 20\%$	100	1000	77.0	85.0	3.0	3.3	4.0	4.5
DH0420H-4R7M	4.7	$\pm 20\%$	100	1000	100.0	110.0	2.2	2.5	3.0	3.5
DH0420H-6R8M	6.8	$\pm 20\%$	100	1000	142.0	159.0	2.0	2.2	2.5	3.0
DH0420H-100M	10	$\pm 20\%$	100	1000	220.0	245.0	1.6	1.8	2.2	2.5
DH0420H-150M	15	$\pm 20\%$	100	1000	310.0	341.0	1.4	1.6	1.8	2.0
DH0420H-220M	22	$\pm 20\%$	100	1000	380.0	420.0	1.0	1.2	1.5	1.6

DH0420喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0420TJ-1R0M	1	$\pm 20\%$	100	1000	25	35	5.5	6.0	10.0	12.0
DH0420HT-4R7M	4.7	$\pm 20\%$	100	1000	91	105	2.6	/	3.5	/
DH0420TJ-100M	10	$\pm 20\%$	100	1000	220	245	1.6	1.8	3.5	4.5
DH0420HT-220M	22	$\pm 20\%$	100	1000	345	400	1.0	1.2	1.5	1.6

DH0512系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0512H-3R3M	3.3	$\pm 20\%$	100	1000	85	103	2.9	3.2	4.0	5.0

DH0515系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0515H-R47M	0.47	$\pm 20\%$	100	1000	10	12	9.0	10.0	11.0	12.0
DH0515H-R68M	0.68	$\pm 20\%$	100	1000	17	22	6.0	8.0	10.0	11.0
DH0515H-1R0M	1	$\pm 20\%$	100	1000	28	34	4.7	5.3	5.5	6.0
DH0515H-2R2M	2.2	$\pm 20\%$	100	1000	76	85	4.0	4.2	5.0	5.5
DH0515H-3R3M	3.3	$\pm 20\%$	100	1000	100	110	2.5	2.8	3.0	3.5
DH0515H-4R7M	4.7	$\pm 20\%$	100	1000	128	145	2.2	2.5	2.5	3.0

DH0518系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0518H-R47M	0.47	$\pm 20\%$	100	1000	10	12	9.0	9.5	13.0	14.0
DH0518H-R68M	0.68	$\pm 20\%$	100	1000	12	15	8.5	9.0	12.5	13.2
DH0518H-1R0M	1	$\pm 20\%$	100	1000	17	22	6.5	7.0	7.5	8.0
DH0518H-1R5M	1.5	$\pm 20\%$	100	1000	28	35	5.0	5.2	7.0	7.5
DH0518H-1R5M01	1.5	$\pm 20\%$	100	1000	23.5	26	6.6	7.5	6.4	8.0
DH0518H-2R2M	2.2	$\pm 20\%$	100	1000	46	56	4.2	4.5	6.5	7.0
DH0518H-2R2M01	2.2	$\pm 20\%$	100	1000	34	42	4.6	4.8	6.5	7.0
DH0518H-3R3M	3.3	$\pm 20\%$	100	1000	68	76	2.8	3.0	4.5	5.0
DH0518H-4R7M	4.7	$\pm 20\%$	100	1000	90	100	2.8	3.0	4.0	4.5
DH0518H-5R6M	5.6	$\pm 20\%$	100	1000	95	105	2.5	2.7	3.8	4.0
DH0518H-6R8M	6.8	$\pm 20\%$	100	1000	148	165	1.9	2.1	3.5	3.8
DH0518H-6R8M01	6.8	$\pm 20\%$	100	1000	125	140	1.9	2.1	3.5	3.8
DH0518H-8R2M	8.2	$\pm 20\%$	100	1000	148	165	1.8	2.0	3.0	3.5
DH0518H-100M	10	$\pm 20\%$	100	1000	170	190	1.7	1.9	3.0	3.5

DH0520系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0520H-R10N	0.1	$\pm 30\%$	100	1000	2.8	3.4	16.0	18.0	30.0	34.0
DH0520H-R22M	0.22	$\pm 20\%$	100	1000	4.4	5.4	11.0	12.0	14.0	15.0
DH0520H-R33M	0.33	$\pm 20\%$	100	1000	7.2	8.8	10.0	10.5	12.0	13.0
DH0520H-R47M	0.47	$\pm 20\%$	100	1000	10	12	9.0	9.5	11.0	12.0
DH0520H-R47M02	0.47	$\pm 20\%$	100	1000	7.8	9	11.5	/	15.5	/
DH0520H-R68M	0.68	$\pm 20\%$	100	1000	12.5	16.5	7.5	8.5	10.0	11.0
DH0520H-1R0M	1	$\pm 20\%$	100	1000	17	22	7.0	8.0	9.0	10.0
DH0520H-1R5M	1.5	$\pm 20\%$	100	1000	26	33	5.5	6.0	7.5	8.0
DH0520H-1R5M01	1.5	$\pm 20\%$	100	1000	24	30	5.5	6.0	7.5	8.0
DH0520H-2R2M	2.2	$\pm 20\%$	100	1000	38	46	4.5	5.0	6.5	7.0

DH0520H-3R3M	3.3	±20%	100	1000	58	65	3.5	3.7	5.5	6.0
DH0520H-4R7M01	4.7	±20%	100	1000	70	80	2.8	3.0	4.5	5.0
DH0520H-4R7M	4.7	±20%	100	1000	89	100	2.8	3.0	4.5	5.0
DH0520H-5R6M	5.6	±20%	100	1000	95	105	2.5	2.8	3.8	4.0
DH0520H-6R8M	6.8	±20%	100	1000	124	140	2.0	2.2	3.8	4.0
DH0520H-8R2M	8.2	±20%	100	1000	135	155	1.9	2.1	3.0	3.5
DH0520H-100M	10	±20%	100	1000	175	195	1.8	2.0	2.8	3.0
DH0520H-220M	22	±20%	100	1000	350	390	1.3	1.5	1.8	2.0



DH0530系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0530H-R10N	0.1	±30%	100	1000	2.5	3	20	22	33	35
DH0530H-R22M	0.22	±20%	100	1000	3.7	4.5	18	20	24	25
DH0530H-R33M	0.33	±20%	100	1000	6	7.5	11	12	18	20
DH0530H-R47M	0.47	±20%	100	1000	6.5	8	10	11	16	18
DH0530H-R56M	0.56	±20%	100	1000	7.3	9	10	11	16	17
DH0530H-R68M	0.68	±20%	100	1000	9	11	9	10	13	14.5
DH0530H-R82M	0.82	±20%	100	1000	9.2	12	8.5	9	12	13
DH0530H-1R0M	1	±20%	100	1000	11	14	8.3	8.8	11	12
DH0530H-1R2M	1.2	±20%	100	1000	11	14	8.3	8.8	10.5	11
DH0530H-1R5M	1.5	±20%	100	1000	15.5	20	7.5	8	10	10.5
DH0530H-2R2M	2.2	±20%	100	1000	25	30	5	5.5	8.5	9
DH0530H-2R2M01	2.2	±20%	100	1000	20	25	5.5	6.5	8.5	10
DH0530H-3R3M	3.3	±20%	100	1000	30	38	4.5	4.8	7	8
DH0530H-4R7M	4.7	±20%	100	1000	47	57	4.2	4.5	5	6
DH0530H-5R6M	5.6	±20%	100	1000	57	63	3.0	3.5	5.0	5.5
DH0530H-5R6M01	5.6	±20%	100	1000	52	60	3.5	4.0	5.5	6.0
DH0530H-6R8M	6.8	±20%	100	1000	70	78	2.8	3	4	5

DH0530H-6R8M01	6.8	±20%	100	1000	60	66	3.0	3.2	4.5	5.0
DH0530H-8R2M	8.2	±20%	100	1000	96	108	2.5	2.8	4.5	5
DH0530H-100M	10	±20%	100	1000	115	130	2	2.5	3.5	3.7
DH0530H-100M01	10	±20%	100	1000	105	125	2.5	3	3.5	4
DH0530H-150M	15	±20%	100	1000	192	215	1.8	2	2.8	3
DH0530H-150M01	15	±20%	100	1000	163	190	2.1	2.3	2.3	2.5
DH0530H-220M	22	±20%	100	1000	230	255	1.3	1.5	2.3	2.5
DH0530H-330M	33	±20%	100	1000	350	390	1	1.2	1.8	2
DH0530H-330M01	33	±20%	100	1000	335	375	1	1.2	1.8	2

DH0540系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0540H-4R7M	4.7	$\pm 20\%$	100	1000	38	48	4.3	4.6	6.0	7.0
DH0540H-100M	10	$\pm 20\%$	100	1000	92	105	2.5	2.8	4.5	5.0
DH0540H-150M	15	$\pm 20\%$	100	1000	140	155	2.0	2.2	2.8	3.0
DH0540H-220M	22	$\pm 20\%$	100	1000	198	220	1.5	1.8	2.3	2.5
DH0540H-330M	33	$\pm 20\%$	100	1000	295	325	1.2	1.3	2.3	2.5
DH0540H-470M	47	$\pm 20\%$	100	1000	390	430	1.0	1.2	1.5	1.8

DH0615系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0615H-R68M	0.68	$\pm 20\%$	100	1000	10.0	12.0	9.0	10.0	11.0	12.0
DH0615H-1R0M	1.0	$\pm 20\%$	100	1000	18.0	22.0	7.8	8.2	8.5	9.0
DH0615H-1R5M	1.5	$\pm 20\%$	100	1000	28.5	35.0	6.2	6.5	7.5	8.0
DH0615H-2R2M	2.2	$\pm 20\%$	100	1000	46.0	56.0	4.0	4.5	5.5	6.0
DH0615H-4R7M	4.7	$\pm 20\%$	100	1000	80.0	88.0	3.5	4.0	4.5	5.0

DH0615喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0615TJ-1R5M	1.5	$\pm 20\%$	100	1000	30	40	7.5	8	12	12.5

DH0618系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0618H-R10N	0.10	$\pm 30\%$	100	1000	2.2	2.7	22.0	24.0	28.0	30.0
DH0618H-R15M	0.15	$\pm 20\%$	100	1000	2.2	2.7	20.0	22.0	28.0	30.0
DH0618H-R22M	0.22	$\pm 20\%$	100	1000	3.5	4.5	14.0	15.0	23.0	25.0
DH0618H-R33M	0.33	$\pm 20\%$	100	1000	4.0	5.0	13.0	14.0	22.0	24.0
DH0618H-R47M	0.47	$\pm 20\%$	100	1000	7.0	8.5	10.5	11.5	18.0	20.0
DH0618H-R68M	0.68	$\pm 20\%$	100	1000	10.0	12.0	9.0	10.0	15.0	16.0
DH0618H-1R0M	1.0	$\pm 20\%$	100	1000	15.0	18.0	7.5	8.0	11.0	12.0
DH0618H-1R5M	1.5	$\pm 20\%$	100	1000	24.0	30.0	6.5	7.0	9.0	10.0
DH0618H-1R5M02	1.5	$\pm 20\%$	100	1000	21.0	26.0	7.0	7.5	10.5	11.0
DH0618H-2R2M	2.2	$\pm 20\%$	100	1000	34.0	42.0	4.5	5.0	7.5	8.0
DH0618H-3R3M	3.3	$\pm 20\%$	100	1000	47.0	58.0	4.0	4.5	6.5	7.0
DH0618H-4R7M	4.7	$\pm 20\%$	100	1000	65.0	72.0	3.8	4.0	5.0	5.5
DH0618H-6R8M	6.8	$\pm 20\%$	100	1000	94.0	104.0	3.0	3.2	4.2	4.5
DH0618H-100M	10	$\pm 20\%$	100	1000	149.0	165.0	2.1	2.3	3.4	3.7

DH0620系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0620H-R10N	0.10	$\pm 30\%$	100	1000	2.0	2.6	22.0	24.0	32.0	35.0
DH0620H-R15M	0.15	$\pm 20\%$	100	1000	2.2	2.8	20.0	22.0	28.0	30.0
DH0620H-R22M	0.22	$\pm 20\%$	100	1000	2.9	3.5	16.0	18.0	23.0	25.0
DH0620H-R33M	0.33	$\pm 20\%$	100	1000	4.5	5.4	14.0	16.0	22.0	24.0
DH0620H-R47M	0.47	$\pm 20\%$	100	1000	6.8	8.2	12.0	14.0	18.0	20.0
DH0620H-R68M	0.68	$\pm 20\%$	100	1000	9.5	12.0	9.0	10.0	16.0	17.0
DH0620H-R82M	0.82	$\pm 20\%$	100	1000	16.5	20.0	8.0	9.0	13.0	14.0
DH0620H-1R0M	1.0	$\pm 20\%$	100	1000	16.5	20.0	8.0	9.0	13.0	14.0
DH0620H-1R5M	1.5	$\pm 20\%$	100	1000	20.5	26.0	6.0	6.5	11.0	12.0
DH0620H-2R2M	2.2	$\pm 20\%$	100	1000	30.0	36.0	5.0	5.5	8.5	9.0
DH0620H-3R3M	3.3	$\pm 20\%$	100	1000	44.0	54.0	4.0	4.5	6.5	7.0
DH0620H-4R7M	4.7	$\pm 20\%$	100	1000	89.0	100.0	3.5	3.8	6.0	6.5
DH0620H-6R8M	6.8	$\pm 20\%$	100	1000	96.0	108.0	3.0	3.2	3.5	4.0
DH0620H-100M	10	$\pm 20\%$	100	1000	155.0	172.0	2.0	2.2	3.0	3.5

DH0624系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0624H-R10N	0.10	$\pm 30\%$	100	1000	1.8	2.2	24.0	26.0	38.0	40.0
DH0624H-R15M	0.15	$\pm 20\%$	100	1000	1.9	2.3	22.0	24.0	40.0	42.0
DH0624H-R22M	0.22	$\pm 20\%$	100	1000	2.7	3.6	20.0	21.0	32.0	34.0
DH0624H-R36M	0.36	$\pm 20\%$	100	1000	4.5	5.5	15.0	17.0	20.0	22.0
DH0624H-R47M	0.47	$\pm 20\%$	100	1000	5.0	6.2	13.0	15.0	17.0	18.0
DH0624H-R68M	0.68	$\pm 20\%$	100	1000	7.0	8.6	12.5	13.5	17.0	18.0
DH0624H-1R0M	1.0	$\pm 20\%$	100	1000	11.0	13.5	10.0	11.0	14.0	15.0
DH0624H-1R5M	1.5	$\pm 20\%$	100	1000	16.0	20.0	8.0	8.5	12.0	13.0
DH0624H-2R2M	2.2	$\pm 20\%$	100	1000	25.0	32.0	6.0	6.5	9.0	10.0
DH0624H-3R3M	3.3	$\pm 20\%$	100	1000	34.0	42.0	5.0	5.5	8.5	9.0
DH0624H-4R7M	4.7	$\pm 20\%$	100	1000	41.0	50.0	4.5	5.0	6.5	7.0
DH0624H-5R6M	5.6	$\pm 20\%$	100	1000	52.0	60.0	4.2	4.5	6.0	6.5
DH0624H-6R8M	6.8	$\pm 20\%$	100	1000	64.0	72.0	4.0	4.2	6.0	6.5
DH0624H-6R8M01	6.8	$\pm 20\%$	100	1000	60.0	66.0	5.0	5.2	5.5	6.0
DH0624H-8R2M	8.2	$\pm 20\%$	100	1000	70.0	77.0	3.8	4.0	5.0	5.5
DH0624H-100M	10	$\pm 20\%$	100	1000	92.0	102.0	2.8	3.1	4.5	5.0
DH0624H-150M	15	$\pm 20\%$	100	1000	145.0	160.0	2.5	2.6	3.3	3.5
DH0624H-220M	22	$\pm 20\%$	100	1000	175.0	195.0	2.2	2.4	2.5	3.0

DH0628系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0628H-1R0M	1.0	$\pm 20\%$	100	1000	8.5	11.0	11.0	12.0	14.0	15.0
DH0628H-1R5M	1.5	$\pm 20\%$	100	1000	10.0	12.5	10.0	11.0	12.0	13.0

DH0630系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0630H-R10M	0.1	$\pm 30\%$	100	1000	1.6	2	29.0	32.0	45.0	50.0
DH0630H-R10MD	0.1	$\pm 30\%$	100	1000	0.85	0.95	35.0	37.0	57.0	60.0
DH0630H-R15M	0.15	$\pm 20\%$	100	1000	1.9	2.4	26.0	28.0	48.0	52.0
DH0630H-R15MD	0.15	$\pm 20\%$	100	1000	0.85	0.95	35.0	37.0	41.0	45.0
DH0630H-R15MD01	0.15	$\pm 20\%$	100	1000	0.9 $\pm$ 5%		35.0	38.0	45.0	50.0
DH0630H-R22M	0.22	$\pm 20\%$	100	1000	2.2	2.8	24.0	24.5	32.0	35.0
DH0630H-R33M	0.33	$\pm 20\%$	100	1000	3.3	4	19.0	20.0	26.0	30.0
DH0630H-R47M	0.47	$\pm 20\%$	100	1000	3.5	4.2	18.0	19.0	21.0	24.0
DH0630H-R56M	0.56	$\pm 20\%$	100	1000	4	4.8	17.0	18.0	20.0	22.0
DH0630H-R68M	0.68	$\pm 20\%$	100	1000	4.8	5.8	15.0	16.0	18.0	20.0
DH0630H-R82M	0.82	$\pm 20\%$	100	1000	5.6	6.8	13.5	14.0	18.0	20.0
DH0630H-1R0M	1	$\pm 20\%$	100	1000	8.5	11	11.5	12.0	15.0	16.0
DH0630H-1R0M01	1	$\pm 20\%$	100	1000	6.9	8.3	13.0	13.5	14.0	15.0
DH0630H-1R5M	1.5	$\pm 20\%$	100	1000	10	13	10.0	11.0	13.0	14.0
DH0630H-1R5M01	1.5	$\pm 20\%$	100	1000	8.1	9.8	11.5	12.0	12.0	13.0
DH0630H-2R2M	2.2	$\pm 20\%$	100	1000	14.5	20	8.0	9.0	11.0	12.0
DH0630H-2R2M01	2.2	$\pm 20\%$	100	1000	12	14.5	9.0	10.0	11.0	11.5
DH0630H-2R2M02	2.2	$\pm 20\%$	100	1000	16	20	8.0	8.5	12.0	14.0
DH0630H-2R7M	2.7	$\pm 20\%$	100	1000	16	20	8.0	8.5	11.0	12.0
DH0630H-3R3M	3.3	$\pm 20\%$	100	1000	24.5	30	6.2	6.5	9.0	10.0
DH0630H-3R3M01	3.3	$\pm 20\%$	100	1000	18	22	8.0	8.5	9.0	10.0
DH0630H-4R7M	4.7	$\pm 20\%$	100	1000	35	42	6.0	6.2	8.0	8.5
DH0630H-4R7M01	4.7	$\pm 20\%$	100	1000	31	38	6.0	6.5	8.0	8.5
DH0630H-4R7M02	4.7	$\pm 20\%$	100	1000	35	42	6.0	6.2	8.5	9.0
DH0630H-5R6M	5.6	$\pm 20\%$	100	1000	42	52	4.8	5.0	7.5	8.0
DH0630H-6R8M	6.8	$\pm 20\%$	100	1000	54	60	4.0	4.2	6.5	7.0
DH0630H-6R8M01	6.8	$\pm 20\%$	100	1000	45	55	4.8	5.0	6.5	7.0

DH0640系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0640H-R22MD	0.22	$\pm 20\%$	100	1000	0.95	1.25	32.0	33.0	35.0	38.0
DH0640H-R33M	0.33	$\pm 20\%$	100	1000	3.1	3.8	18.0	19.0	26.0	28.0
DH0640H-R68M	0.68	$\pm 20\%$	100	1000	4	4.8	17.0	18.0	16.0	18.0
DH0640H-1R0M	1	$\pm 20\%$	100	1000	5.5	6.8	13.0	14.0	15.0	16.0
DH0640H-1R5M	1.5	$\pm 20\%$	100	1000	8.2	10	12.0	13.0	12.0	14.0
DH0640H-1R5M01	1.5	$\pm 20\%$	100	1000	6	7.5	12.5	13.0	12.0	13.0
DH0640H-2R2M	2.2	$\pm 20\%$	100	1000	9.5	12	10.5	11.5	12.0	14.0
DH0640H-3R3M	3.3	$\pm 20\%$	100	1000	15	20	8.0	9.0	10.0	12.0
DH0640H-4R7M	4.7	$\pm 20\%$	100	1000	22	28	7.0	8.0	9.0	10.0
DH0640H-6R8M	6.8	$\pm 20\%$	100	1000	40	48	5.0	5.5	7.0	8.0
DH0640H-100M	10	$\pm 20\%$	100	1000	56	64	4.5	5.0	5.0	5.5
DH0640H-100M02	10	$\pm 20\%$	100	1000	60	68	6.0	6.5	6.0	6.5
DH0640H-150M	15	$\pm 20\%$	100	1000	90	100	3.5	4.0	4.5	5.0
DH0640H-220M	22	$\pm 20\%$	100	1000	120	135	2.5	3.0	3.0	3.5
DH0640H-330M	33	$\pm 20\%$	100	1000	195	215	2.0	2.5	3.0	3.5
DH0640H-470M	47	$\pm 20\%$	100	1000	245	275	1.8	2.0	2.5	3.0

DH0640喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0640TJ-R15MD	0.15	$\pm 20\%$	100	1000	0.7	0.91	32	40	60	65
DH0640TJ-R36MD	0.36	$\pm 20\%$	100	1000	1.58	1.9	26	27	28	30
DH0640TJ-1R5M	1.5	$\pm 20\%$	100	1000	7.5	9.5	10	12	18	20
DH0640HT-4R7M	4.7	$\pm 20\%$	100	1000	22	28	5.5	6	11	11.5
DH0640HY-470M	47	$\pm 20\%$	100	1000	230	255	1.5	1.8	2.3	2.5

DH0648系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0648H-470M	47	$\pm 20\%$	100	1000	162	178	2.3	2.8	2.5	3.0

DH0650系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0650H-R22M	0.22	$\pm 20\%$	100	1000	1.9	2.3	28.0	30.0	38.0	40.0
DH0650H-R36M	0.36	$\pm 20\%$	100	1000	2.4	3.0	20.0	21.0	24.0	26.0
DH0650H-R47M	0.47	$\pm 20\%$	100	1000	2.8	3.5	19.0	20.0	20.0	22.0
DH0650H-R56M	0.56	$\pm 20\%$	100	1000	3.4	4.2	18.0	19.0	19.0	20.0
DH0650H-R68M	0.68	$\pm 20\%$	100	1000	4.0	5.0	17.0	18.0	17.0	18.0
DH0650H-1R0M	1.0	$\pm 20\%$	100	1000	5.2	6.3	13.0	14.0	15.0	16.0
DH0650H-1R5M	1.5	$\pm 20\%$	100	1000	7.2	8.8	12.0	13.0	13.0	14.0
DH0650H-2R2M	2.2	$\pm 20\%$	100	1000	10.0	12.0	10.0	11.0	11.0	12.0
DH0650H-3R3M	3.3	$\pm 20\%$	100	1000	13.8	18.0	9.0	10.0	10.0	11.0
DH0650H-4R7M	4.7	$\pm 20\%$	100	1000	18.5	24.0	8.0	9.0	9.0	10.0
DH0650H-5R6M	5.6	$\pm 20\%$	100	1000	25.0	32.0	7.0	7.5	8.0	9.0
DH0650H-6R8M	6.8	$\pm 20\%$	100	1000	27.0	35.0	6.5	7.0	7.5	8.0
DH0650H-8R2M	8.2	$\pm 20\%$	100	1000	38.0	46.0	6.0	6.5	7.0	7.5
DH0650H-100M	10	$\pm 20\%$	100	1000	45.0	55.0	5.0	5.5	6.5	7.0
DH0650H-150M	15	$\pm 20\%$	100	1000	60.0	66.0	4.5	5.0	5.5	6.0
DH0650H-220M	22	$\pm 20\%$	100	1000	115.0	128.0	3.0	3.5	3.5	4.0
DH0650H-220M01	22	$\pm 20\%$	100	1000	90.0	100.0	3.2	3.8	3.5	4.0
DH0650H-330M	33	$\pm 20\%$	100	1000	154.0	172.0	2.2	2.5	3.0	3.5
DH0650H-330M01	33	$\pm 20\%$	100	1000	140.0	155.0	2.5	3.0	3.5	4.0
DH0650H-470M	47	$\pm 20\%$	100	1000	230.0	255.0	1.8	2.0	2.5	3.0
DH0650H-680M	68	$\pm 20\%$	100	1000	320.0	355.0	1.0	1.2	1.8	2.1

DH0650H-680M02	68	±20%	100	1000	265.0	295.0	1.5	2.0	2.2	2.5
DH0650H-101M	100	±20%	100	1000	485.0	535.0	0.8	1.0	1.5	1.8

DH0650喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0650TJ-R15MD	0.15	±20%	100	1000	0.98	1.3	30.0	40.0	60.0	65.0
DH0650TJ-R47MD	0.47	±20%	100	1000	2.2	2.8	18.0	20.0	25.0	28.0
DH0650HY-1R0M	1	±20%	100	1000	5.5	8.5	8.0	12.0	14.0	15.0
DH0650TJ-2R2M	2.2	±20%	100	1000	9.5	12	10.5	11.5	13.0	15.0
DH0650HT-3R3M	3.3	±20%	100	1000	14.5	20	7.6	8.5	9.0	10.0
DH0650HT-4R7M	4.7	±20%	100	1000	18.5	24	5.5	6.0	8.0	9.0
DH0650TJ-6R8M	6.8	±20%	100	1000	27	35	5.5	6.5	12.0	14.0
DH0650TJ-8R2M	8.2	±20%	100	1000	45	54	4.5	5.0	12.0	14.0
DH0650TJ-8R2M01	8.2	±20%	100	1000	32	40	4.5	5.0	13.0	14.0
DH0650HT-100M	10	±20%	100	1000	31.5	38	4.5	5.0	7.0	8.0
DH0650TJ-100M	10	±20%	100	1000	45	54	4.5	5.0	12.0	14.0
DH0650TJ-100M01	10	±20%	100	1000	32	40	4.5	5.0	13.0	14.0
DH0650HY-150M	15	±20%	100	1000	60	70	3.8	4.5	5.0	5.5
DH0650HT-150M	15	±20%	100	1000	50	58	4.0	4.5	5.0	5.5
DH0650TJ-150M	15	±20%	100	1000	72	82	3.5	4.0	7.0	7.5
DH0650HY-220M	22	±20%	100	1000	75	85	3.5	4.0	3.5	4.0
DH0650HY-220M01	22	±20%	100	1000	68	75	3.6	4.2	3.5	4.0
DH0650HT-220M	22	±20%	100	1000	95	110	4.0	4.2	5.5	6.0
DH0650HY-330M	33	±20%	100	1000	150	170	2.0	2.2	3.0	3.5
DH0650HT-330M	33	±20%	100	1000	140	160	2.5	3.2	3.5	4.0
DH0650HY-470M	47	±20%	100	1000	185	210	1.8	2.0	2.0	2.2
DH0650HT-470M	47	±20%	100	1000	230	255	2.0	2.5	3.0	3.5
DH0650HY-680M	68	±20%	100	1000	240	265	1.5	1.8	1.8	2.0
DH0650HY-820M	82	±20%	100	1000	360	430	1.2	1.5	1.8	2.0
DH0650HY-101M	100	±20%	100	1000	365	440	1.0	1.2	1.6	1.8
DH0650HY-101M01	100	±20%	100	1000	395	440	1.0	1.2	1.6	1.8

DH0658喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0658TJ-100M	10	±20%	100	1000	45	55	4.5	5.0	13.0	15.0

DH0660喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0660TJ-100M	10	$\pm 20\%$	100	1000	45	55	4.5	5.0	13.0	15.0

DH0820系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0820H-1R0M	1.00	$\pm 20\%$	100	1000	9.6	14.0	10.2	11.4	15.0	16.6

DH0830系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0830H-R33M	0.33	$\pm 20\%$	100	1000	2.5	3.0	20.0	21.0	28.0	30.0
DH0830H-R47M	0.47	$\pm 20\%$	100	1000	3.1	3.8	19.0	20.0	28.0	30.0
DH0830H-R68M	0.68	$\pm 20\%$	100	1000	3.6	4.4	18.0	19.0	24.0	26.0
DH0830H-R82M	0.82	$\pm 20\%$	100	1000	5.2	6.3	13.0	14.0	20.0	22.0
DH0830H-1R0M	1.0	$\pm 20\%$	100	1000	5.2	6.5	13.0	14.0	18.0	20.0
DH0830H-1R5M	1.5	$\pm 20\%$	100	1000	6.3	7.6	12.0	13.0	15.0	16.0
DH0830H-2R2M	2.2	$\pm 20\%$	100	1000	10.0	12.0	10.0	11.0	13.0	14.0
DH0830H-3R3M	3.3	$\pm 20\%$	100	1000	15.0	18.0	8.0	9.5	9.0	10.0
DH0830H-4R7M	4.7	$\pm 20\%$	100	1000	24.0	30.0	7.0	8.0	9.0	10.0
DH0830H-5R6M	5.6	$\pm 20\%$	100	1000	30.0	38.0	6.0	7.0	7.0	8.0
DH0830H-6R8M	6.8	$\pm 20\%$	100	1000	45.0	55.0	5.0	6.0	8.0	9.0
DH0830H-100M	10	$\pm 20\%$	100	1000	54.0	60.0	4.8	5.5	6.0	6.5
DH0830H-150M	15	$\pm 20\%$	100	1000	90.0	100.0	3.5	4.0	4.5	5.0
DH0830H-220M	22	$\pm 20\%$	100	1000	100.0	110.0	3.0	3.8	4.0	4.5

DH0830H-330M	33	±20%	100	1000	155.0	172.0	2.0	2.5	3.0	3.5
DH0830H-470M	47	±20%	100	1000	260.0	288.0	1.5	2.0	2.0	2.5

DH0830喷漆系列

型号规格 Part NO.	标称感量 Inductance (μH)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (mΩ)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0830TJ-8R2M	8.2	±20%	100	1000	44	54	5.5	6	8	8.5

DH0840系列

型号规格 Part NO.	标称感量 Inductance (μH)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (mΩ)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0840H-R33MD	0.33	±20%	100	1000	1.6	2.2	27	29.0	35.0	36.0
DH0840H-1R0M	1.0	±20%	100	1000	4.15	5	16	17.0	19.0	20.0
DH0840H-2R2M	2.2	±20%	100	1000	9.5	12.0	10.5	11.5	15.0	16.0
DH0840H-3R3M	3.3	±20%	100	1000	12	15.0	9.0	10.0	11.0	12.0
DH0840H-4R7M	4.7	±20%	100	1000	17	22.0	7.5	8.0	10.0	10.5
DH0840H-6R8M	6.8	±20%	100	1000	29	35.0	6.0	7.0	9.0	10.0
DH0840H-8R2M	8.2	±20%	100	1000	42	52.0	5.0	6.5	7.5	8.0
DH0840H-100M	10	±20%	100	1000	42	52.0	5.0	6.5	7.5	8.0
DH0840H-150M	15	±20%	100	1000	60	70.0	4.5	5.0	6.0	7.0
DH0840H-220M	22	±20%	100	1000	93	105	3.5	4.2	5.0	5.5
DH0840H-330M	33	±20%	100	1000	128	150	2.5	2.8	3.2	3.5
DH0840H-470M	47	±20%	100	1000	170	190	2	2.5	2.5	3.0

DH0850系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0850H-R15M	0.15	$\pm 20\%$	100	1000	0.6	0.7	38.0	40.0	58.0	60.0
DH0850H-R22M	0.22	$\pm 20\%$	100	1000	1.8	2.2	25.0	26.0	53.0	55.0
DH0850H-R22M01	0.22	$\pm 20\%$	100	1000	0.6	0.8	30.0	32.0	53.0	55.0
DH0850H-R47M	0.47	$\pm 20\%$	100	1000	2.5	2.9	22.0	23.0	28.0	30.0
DH0850H-R68M	0.68	$\pm 20\%$	100	1000	3.6	4.4	18.0	19.0	23.0	25.0
DH0850H-R82M	0.82	$\pm 20\%$	100	1000	4.0	4.8	17.0	18.0	23.0	24.0
DH0850H-1R0M	1.0	$\pm 20\%$	100	1000	4.1	5.0	16.0	17.0	19.0	20.0
DH0850H-1R5M	1.5	$\pm 20\%$	100	1000	4.9	6.0	14.0	15.0	19.0	20.0
DH0850H-1R8M	1.8	$\pm 20\%$	100	1000	7.5	9.0	13.0	14.0	17.0	18.0
DH0850H-2R2M	2.2	$\pm 20\%$	100	1000	8.2	10.0	11.0	12.0	15.0	16.0
DH0850H-2R2M02	2.2	$\pm 20\%$	100	1000	8.2	10.0	11.0	12.0	15.0	16.0
DH0850H-3R3M	3.3	$\pm 20\%$	100	1000	11.0	13.5	10.0	10.5	12.0	13.0
DH0850H-4R7M	4.7	$\pm 20\%$	100	1000	15.0	18.0	8.5	9.5	11.0	12.0
DH0850H-5R6M	5.6	$\pm 20\%$	100	1000	19.8	24.0	8.0	9.0	12.0	13.0
DH0850H-6R8M	6.8	$\pm 20\%$	100	1000	20.0	25.0	8.0	9.0	10.0	11.0
DH0850H-100M	10	$\pm 20\%$	100	1000	35.0	42.0	6.0	6.5	7.0	8.0
DH0850H-150M	15	$\pm 20\%$	100	1000	47.0	58.0	5.0	6.0	6.5	7.0
DH0850H-220M	22	$\pm 20\%$	100	1000	74.0	84.0	4.0	4.5	5.0	5.5
DH0850H-330M	33	$\pm 20\%$	100	1000	120.0	135.0	2.5	3.5	4.5	5.0
DH0850H-470M	47	$\pm 20\%$	100	1000	177.0	195.0	2.0	2.5	3.0	3.5
DH0850H-560M	56	$\pm 20\%$	100	1000	170.0	190.0	2.2	2.5	3.0	3.5
DH0850H-680M	68	$\pm 20\%$	100	1000	235.0	260.0	1.5	2.0	2.5	3.0
DH0850H-101M	100	$\pm 20\%$	100	1000	272.0	300.0	1.0	1.5	2.0	2.5

DH0860系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0860H-220M	22	$\pm 20\%$	100	1000	53	70	6.0	6.2	7.0	7.2

DH0860喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH0860HT-220M	22	$\pm 20\%$	100	1000	53	70	5.5	6.0	6.5	7.0

DH1020系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1020H-2R2M	2.2	$\pm 20\%$	100	1000	25	30	7.0	8.0	9.5	10.0
DH1020H-3R3M	3.3	$\pm 20\%$	100	1000	30	36	6.0	7.0	8.5	9.5

DH1020喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1020HT-100M	10	$\pm 20\%$	100	1000	60	70	3.8	4	5.5	6

DH1024系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1024H-2R2M	2.2	$\pm 20\%$	100	1000	14.5	20	8.5	9.5	10.0	11.0

DH1025系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1025H-1R0M	1	$\pm 20\%$	100	1000	6.4	9.6	13.0	14.0	17.0	18.0

DH1030系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1030H-R22M	0.22	$\pm 20\%$	100	1000	0.7	0.9	30.0	32.0	40.0	41.0
DH1030H-R56M	0.56	$\pm 20\%$	100	1000	3.1	3.8	19.0	22.0	28.0	30.0
DH1030H-1R0M	1.0	$\pm 20\%$	100	1000	6.4	7.8	13.0	14.0	22.0	24.0
DH1030H-2R2M	2.2	$\pm 20\%$	100	1000	11.0	13.5	9.0	10.0	15.0	16.0
DH1030H-3R3M	3.3	$\pm 20\%$	100	1000	16.5	20.0	7.0	8.0	13.0	14.0
DH1030H-4R7M	4.7	$\pm 20\%$	100	1000	25.0	30.0	5.5	6.0	10.5	12.0
DH1030H-6R8M	6.8	$\pm 20\%$	100	1000	42.0	52.0	5.0	5.2	9.0	10.0
DH1030H-8R2M	8.2	$\pm 20\%$	100	1000	49.0	60.0	4.8	5.0	8.5	9.0
DH1030H-100M	10	$\pm 20\%$	100	1000	53.5	62.0	4.5	5.0	7.0	8.0
DH1030H-220M	22	$\pm 20\%$	100	1000	93.0	105.0	3.0	3.5	5.5	6.0
DH1030H-330M	33	$\pm 20\%$	100	1000	125.0	140.0	2.0	2.5	3.5	4.0

DH1030喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1030TJ-4R7M	4.7	$\pm 20\%$	100	1000	25	35	9	10	14.5	15
DH1030HY-6R8M	6.8	$\pm 20\%$	100	1000	32	40	4.5	5	5.5	6

DH1040系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电 压 Test Voltage (mV)	直流电阻 Rdc ($m\Omega$)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1040H-R15MD	0.15	$\pm 20\%$	100	1000	0.42	0.52	42	45.0	70.0	75.0
DH1040H-R19MD	0.19	$\pm 20\%$	100	1000	0.55	0.8	35	37.0	60.0	65.0
DH1040H-R22MD	0.22	$\pm 20\%$	100	1000	0.55	0.8	35	37.0	55.0	60.0
DH1040H-R33MD	0.33	$\pm 20\%$	100	1000	1	1.5	28	30.0	48.0	50.0
DH1040H-R36MD	0.36	$\pm 20\%$	100	1000	1	1.5	28	30.0	48.0	50.0
DH1040H-R36MD01	0.36	$\pm 20\%$	100	1000	0.9	1.2	30	32.0	48.0	50.0
DH1040H-R47MD	0.47	$\pm 20\%$	100	1000	1.15	1.5	26	27.0	40.0	42.0
DH1040H-R56MD	0.56	$\pm 20\%$	100	1000	1.7	2.3	24	25.0	30.0	34.0
DH1040H-R68MD	0.68	$\pm 20\%$	100	1000	1.95	2.4	22	23.0	30.0	32.0
DH1040H-R82MD	0.82	$\pm 20\%$	100	1000	2	2.5	20	21.0	28.0	30.0
DH1040H-1R0MD	1	$\pm 20\%$	100	1000	2.4	3	18	19.0	27.0	28.0
DH1040H-1R0M	1	$\pm 20\%$	100	1000	3.4	5	16	17.0	27.0	28.0
DH1040H-1R5M	1.5	$\pm 20\%$	100	1000	4.8	6	14.0	15.0	19.0	20.0
DH1040H-1R5M01	1.5	$\pm 20\%$	100	1000	3.8	4.8	14.0	16.0	20.0	22.0
DH1040H-2R2MD	2.2	$\pm 20\%$	100	1000	4.5	5.5	14.0	15.0	16.0	18.0
DH1040H-2R2M	2.2	$\pm 20\%$	100	1000	7	8.4	11.0	13.0	18.0	19.0
DH1040H-2R2M01	2.2	$\pm 20\%$	100	1000	5.9	6.5	12.0	15.0	16.0	18.0
DH1040H-2R7M	2.7	$\pm 20\%$	100	1000	6.9	9	11.0	13.0	17.0	18.0
DH1040H-3R3M	3.3	$\pm 20\%$	100	1000	10	12	11	12.0	16.0	18.0
DH1040H-4R7M	4.7	$\pm 20\%$	100	1000	14	18	8.5	9.0	13.0	14.0
DH1040H-5R6M	5.6	$\pm 20\%$	100	1000	16.5	20	8.2	8.8	12.0	14.0
DH1040H-6R8M	6.8	$\pm 20\%$	100	1000	18	22	8	8.5	10.0	11.0
DH1040H-8R2M	8.2	$\pm 20\%$	100	1000	26	32	7.0	7.2	10.0	11.0
DH1040H-100M	10	$\pm 20\%$	100	1000	31	38	6	6.5	8.5	9.0

DH1040H-100M01	10	±20%	100	1000	28.5	36	6.5	7.0	8.5	9.0
DH1040H-100M0102	10	±20%	100	1000	28	32	6.5	7.0	9.5	10.5
DH1040H-120M	12	±20%	100	1000	31	38	6	6.5	8.5	9.0
DH1040H-150M	15	±20%	100	1000	45	57	5	5.5	7.5	8.0
DH1040H-220M	22	±20%	100	1000	63.5	72	4.5	5.0	6.0	6.5
DH1040H-220M01	22	±20%	100	1000	58	65	4.5	5.0	6.0	6.5
DH1040H-330M	33	±20%	100	1000	90	100	3.6	4.0	5.0	6.0
DH1040H-390M	39	±20%	100	1000	120	135	3	3.5	4.0	5.0
DH1040H-470M	47	±20%	100	1000	130	145	3.0	3.3	4.5	5.0
DH1040H-680M	68	±20%	100	1000	215	240	2.1	2.3	3.5	4.0
DH1040H-820M	82	±20%	100	1000	230	260	1.9	2.1	3.0	3.5
DH1040H-101M	100	±20%	100	1000	270	300	1.8	2.0	2.8	3.0

DH1040喷漆系列

型号规格 Part NO.	标称感量 Inductance (μH)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (mΩ)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1040TJ-R36MD	0.36	±20%	100	1000	1	1.5	30.0	31.0	60.0	75.0
DH1040HY-R33MD	0.33	±20%	100	1000	0.7	1	24.0	25.0	48.0	50.0
DH1040HY-1R0MD	1	±20%	100	1000	2.4	3.5	18.0	20.0	24.0	26.0
DH1040TJ-1R5M	1.5	±20%	100	1000	4.8	6.3	16.0	18.0	20.0	21.0
DH1040HT-1R5M	1.5	±20%	100	1000	4.3	5.5	16.0	18.0	23.0	25.0
DH1040HY-2R2M	2.2	±20%	100	1000	5.4	7.5	15	17	17.5	18
DH1040TJ-3R3M	3.3	±20%	100	1000	9	12	14.0	16.0	18.0	19.0
DH1040TJ-4R7M	4.7	±20%	100	1000	14	18	7.5	9.0	19.0	22.0
DH1040HY-4R7M	4.7	±20%	100	1000	12	18	8.0	10.0	11.0	13.0
DH1040HY-100M	10	±20%	100	1000	26	35	7.0	8.0	8.0	9.0
DH1040HY-150M	15	±20%	100	1000	45	58	6.2	6.5	7.0	8.0
DH1040HT-150M	15	±20%	100	1000	36	45	6.5	7.0	7.0	8.0
DH1040HY-220M	22	±20%	100	1000	54	65	5.6	6.0	6.0	7.0
DH1040TJ-220M	22	±20%	100	1000	65	74	5.0	5.5	8.0	9.0

DH1040TJ-220M01	22	±20%	100	1000	50	60	6.1	6.5	7.7	8.0
DH1040HY-330M	33	±20%	100	1000	78	90	3.5	4.0	5.0	5.5
DH1040HY-470M	47	±20%	100	1000	120	135	3.2	3.5	4.5	5.0

DH1045系列

型号规格 Part NO.	标称感量 Inductance (μH)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (mΩ)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1045H-2R2M	2.2	±20%	100	1000	6.5	8.0	11.0	13.0	16.0	18.0
DH1045H-4R7M	4.7	±20%	100	1000	14.0	17.0	8.0	8.5	14.0	15.0
DH1045H-100M	10	±20%	100	1000	28.5	35.0	6.5	7.0	8.5	9.0
DH1045H-220M	22	±20%	100	1000	63.5	70.0	4.5	5.0	6.5	7.0
DH1045H-330M	33	±20%	100	1000	89.0	100.0	3.6	4.0	5.5	6.0
DH1045H-470M	47	±20%	100	1000	130.0	145.0	3.0	3.5	4.5	5.0
DH1045H-680M	68	±20%	100	1000	155.0	175.0	2.5	3.0	3.5	4.0
DH1045H-101M	100	±20%	100	1000	300.0	332.0	2.0	2.2	2.8	3.0

DH1050系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1050H-R22M	0.22	$\pm 20\%$	100	1000	0.6	0.7	35.0	37.0	55.0	60.0
DH1050H-1R0M	1.0	$\pm 20\%$	100	1000	2.1	2.6	20.0	22.0	22.0	25.0
DH1050H-1R5M	1.5	$\pm 20\%$	100	1000	4.3	5.2	14.0	15.0	19.0	20.0
DH1050H-1R5M01	1.5	$\pm 20\%$	100	1000	2.9	3.5	19.0	20.0	23.0	24.0
DH1050H-2R2M	2.2	$\pm 20\%$	100	1000	5.0	6.0	12.0	14.0	21.0	22.0
DH1050H-2R2M01	2.2	$\pm 20\%$	100	1000	4.5	5.5	14.0	15.0	21.0	22.0
DH1050H-3R3M	3.3	$\pm 20\%$	100	1000	6.9	8.4	13.0	14.0	15.0	16.0
DH1050H-4R7M	4.7	$\pm 20\%$	100	1000	12.0	15.0	8.5	10.0	14.0	15.0
DH1050H-6R8M	6.8	$\pm 20\%$	100	1000	19.4	25.0	8.0	8.5	13.0	14.0
DH1050H-8R2M	8.2	$\pm 20\%$	100	1000	25.4	32.0	7.0	7.2	12.0	13.0
DH1050H-100M	10	$\pm 20\%$	100	1000	25.5	32.0	7.0	7.2	11.0	12.0
DH1050H-150M	15	$\pm 20\%$	100	1000	36.0	45.0	5.8	6.2	9.0	10.0
DH1050H-220M	22	$\pm 20\%$	100	1000	58.0	65.0	5.5	6.0	7.0	8.0
DH1050H-330M	33	$\pm 20\%$	100	1000	76.0	85.0	4.0	4.5	5.0	6.0
DH1050H-470M	47	$\pm 20\%$	100	1000	110.0	125.0	3.0	3.5	4.5	5.0
DH1050H-560M	56	$\pm 20\%$	100	1000	148.0	165.0	2.7	3.0	4.5	5.0
DH1050H-680M	68	$\pm 20\%$	100	1000	155.0	175.0	2.3	2.5	4.0	4.5
DH1050H-820M	82	$\pm 20\%$	100	1000	215.0	240.0	1.8	2.0	3.0	3.5
DH1050H-101M	100	$\pm 20\%$	100	1000	240.0	265.0	2.6	3.0	3.8	4.0
DH1050H-101M02	100	$\pm 20\%$	100	1000	255.0	285.0	3.0	3.5	4.5	5.0

DH1054系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1054H-1R0MD	1	$\pm 20\%$	100	1000	2.3	2.76	27	30	31.7	37

DH1060系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1060H-2R2M	2.2	$\pm 20\%$	100	1000	4.8	5.8	16	18	22	24
DH1060H-4R7M	4.7	$\pm 20\%$	100	1000	10	13	11	13.0	16.0	18.0
DH1060H-100M	10	$\pm 20\%$	100	1000	16	19	9.5	10	13	13.5

DH1060喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1060TJ-100M	10	$\pm 20\%$	100	1000	16.5	20	8	10	16	18

DH1075系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1075H-R50MD	0.5	$\pm 20\%$	100	1000	0.9	1.1	25	27.0	45.0	55.0
DH1075H-100M	10	$\pm 20\%$	100	1000	16	19	13.2	14.7	14.5	16.0

DH1075喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1075HT-1R0MD	1	$\pm 20\%$	100	1000	1.6	1.9	20	22	30	32

DHCM1080系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DHCM1080H-100M	3.3	$\pm 20\%$	100	1000	35	45	7.0	8.0	11.0	12.0
DHCM1080TJ-100M	3.3	$\pm 20\%$	100	1000	35	45	7.0	8.0	15.0	18.0
DHCM1080H-150M	4.7	$\pm 20\%$	100	1000	50	59	4.0	4.6	8.5	9.1
DHCM1080TJ-150M	10	$\pm 20\%$	100	1000	50	59	4.0	4.6	12.0	14.0
DHCM1080H-220M	15	$\pm 20\%$	100	1000	75	85	2.5	3.1	6.5	7.1
DHCM1080H-270M	15	$\pm 20\%$	100	1000	75	85	2.5	3.1	6.5	7.1
DHCM1080H-330M	22	$\pm 20\%$	100	1000	115	130	2.3	2.6	6.0	7.0
DHCM1080H-470M	22	$\pm 20\%$	100	1000	145	160	2.0	2.5	5.0	6.0

DH1080喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1080HY-220M01	22	$\pm 20\%$	100	1000	30	36	6	7	9	10
DH1080HY-330M	33	$\pm 20\%$	100	1000	52	58	5.2	5.8	7	8
DH1082HY-470M	47	$\pm 20\%$	100	1000	52	58	5.0	5.5	5.5	6.5

DH1175系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1175H-R10MD	0.1	$\pm 20\%$	100	1000	0.35	0.45	40.0	45.0	60.0	65.0
DH1175H-R15MD	0.15	$\pm 20\%$	100	1000	0.57	0.7	36.0	40.0	53.0	55.0
DH1175H-R22MD	0.22	$\pm 20\%$	100	1000	0.68	0.82	30.0	35.0	48.0	50.0
DH1175H-R27MD	0.27	$\pm 20\%$	100	1000	0.78	0.95	26.0	30.0	43.0	45.0

DH1230系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电 压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1230H-4R7M	4.7	$\pm 20\%$	100	1000	18	24	6.0	8.0	10.0	12.0

DH1230喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电 压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1230HY-2R2M	2.2	$\pm 20\%$	100	1000	7.8	10.5	14.0	16.0	12.0	12.5
DH1230HY-6R8M	6.8	$\pm 20\%$	100	1000	16.5	25	7.0	8.0	7.0	7.5

DH1235系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1235H-4R7M	4.7	$\pm 20\%$	100	1000	17	22	8.0	10	13	15
DH1235H-R47M	0.47	$\pm 20\%$	100	1000	1.3	1.6	26.0	28.0	43.0	45.0
DH1235H-R68M	0.68	$\pm 20\%$	100	1000	2.0	2.4	23.0	24.0	38.0	40.0
DH1235H-1R0M	1.0	$\pm 20\%$	100	1000	2.9	3.5	17.0	18.0	34.0	36.0
DH1235H-1R5M	1.5	$\pm 20\%$	100	1000	4.4	5.3	15.0	16.0	28.0	30.0
DH1235H-2R2M	2.2	$\pm 20\%$	100	1000	5.0	6.0	14.0	15.0	18.0	20.0
DH1235H-3R3M	3.3	$\pm 20\%$	100	1000	11.5	14.0	10.0	11.0	16.0	18.0
DH1235H-100M	10	$\pm 20\%$	100	1000	35.0	45.0	6.0	6.5	7.0	8.0
DH1235H-220M	22	$\pm 20\%$	100	1000	65.0	75.0	4.5	5.0	6.5	7.0

DH1240系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1240H-R47M	0.47	$\pm 20\%$	100	1000	1.3	1.6	26.0	28.0	43.0	45.0
DH1240H-R68M	0.68	$\pm 20\%$	100	1000	2.0	2.4	23.0	24.0	38.0	40.0
DH1240H-1R0M	1.0	$\pm 20\%$	100	1000	2.9	3.5	18.0	19.0	36.0	38.0
DH1240H-1R5M	1.5	$\pm 20\%$	100	1000	4.4	5.3	15.0	16.0	28.0	30.0
DH1240H-2R2M	2.2	$\pm 20\%$	100	1000	5.0	6.0	14.0	15.0	18.0	20.0
DH1240H-3R3M	3.3	$\pm 20\%$	100	1000	11.5	14.0	11.0	12.0	16.0	18.0
DH1240H-4R7M	4.7	$\pm 20\%$	100	1000	14.5	18.0	9.0	10.0	15.0	16.0
DH1240H-6R8M	6.8	$\pm 20\%$	100	1000	19.0	24.0	7.0	8.0	10.0	11.0
DH1240H-100M	10	$\pm 20\%$	100	1000	35.0	44.0	5.0	5.5	7.5	8.0
DH1240H-220M	22	$\pm 20\%$	100	1000	65.0	75.0	4.5	5.0	6.5	7.0
DH1240H-330M	33	$\pm 20\%$	100	1000	78.0	90.0	4.0	4.5	5.5	6.0

DH1250系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1250H-R22M	0.22	$\pm 20\%$	100	1000	0.6	0.8	42.0	45.0	45.0	50.0
DH1250H-R33M	0.33	$\pm 20\%$	100	1000	1.0	1.2	37.0	38.0	44.0	48.0
DH1250H-R47M	0.47	$\pm 20\%$	100	1000	1.1	1.4	35.0	36.0	42.0	45.0
DH1250H-R68M	0.68	$\pm 20\%$	100	1000	1.4	1.7	26.0	28.0	34.0	38.0
DH1250H-1R0M	1.0	$\pm 20\%$	100	1000	2.1	2.6	24.0	26.0	30.0	35.0
DH1250H-1R5M	1.5	$\pm 20\%$	100	1000	2.6	3.2	22.0	23.0	26.0	30.0
DH1250H-2R2M	2.2	$\pm 20\%$	100	1000	4.8	5.8	16.0	17.0	22.0	26.0
DH1250H-3R3M	3.3	$\pm 20\%$	100	1000	6.2	7.5	15.0	16.0	21.0	24.0
DH1250H-4R7M	4.7	$\pm 20\%$	100	1000	10.5	13.0	12.0	13.0	19.0	20.0
DH1250H-4R7M01	4.7	$\pm 20\%$	100	1000	8.5	10.5	13.0	14.0	17.0	18.0
DH1250H-6R8M	6.8	$\pm 20\%$	100	1000	15.8	20.0	9.0	10.0	15.0	16.0
DH1250H-8R2M	8.2	$\pm 20\%$	100	1000	21.5	27.0	8.5	9.0	15.0	16.0
DH1250H-100M	10	$\pm 20\%$	100	1000	27.5	35.0	6.5	7.0	13.0	14.0
DH1250H-150M	15	$\pm 20\%$	100	1000	36.0	45.0	6.0	6.5	10.0	11.0
DH1250H-220M	22	$\pm 20\%$	100	1000	46.0	57.0	5.5	6.0	8.5	9.0
DH1250H-330M	33	$\pm 20\%$	100	1000	72.0	82.0	4.5	5.0	6.5	7.0
DH1250H-470M	47	$\pm 20\%$	100	1000	85.0	95.0	4.0	4.5	5.5	6.0
DH1250H-680M	68	$\pm 20\%$	100	1000	135.0	150.0	3.0	3.5	4.5	5.0
DH1250H-101M	100	$\pm 20\%$	100	1000	160.0	180.0	2.5	3.0	3.5	4.0

DH1250喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1250HY-1R0MD	1	$\pm 20\%$	100	1000	2.1	3.2	20.0	22.0	35.0	36.0
DH1250TJ-2R2M	2.2	$\pm 20\%$	100	1000	4.7	5.5	20.0	22.0	32.0	34.0
DH1250HY-4R7M	4.7	$\pm 20\%$	100	1000	10.5	15	10.0	12.0	16.0	17.0
DH1250HY-220M	22	$\pm 20\%$	100	1000	35	45	5.5	6.0	7.0	7.5

DH1260系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1260H-R22M	0.22	$\pm 20\%$	100	1000	0.5	0.6	42.0	45.0	55.0	60.0
DH1260H-R33M	0.33	$\pm 20\%$	100	1000	0.6	0.75	38.0	40.0	55.0	60.0
DH1260H-R82M	0.82	$\pm 20\%$	100	1000	1.5	1.8	26.0	28.0	33.0	35.0
DH1260H-1R0M	1.0	$\pm 20\%$	100	1000	2.1	2.6	24.0	26.0	33.0	35.0
DH1260H-1R5M	1.5	$\pm 20\%$	100	1000	2.2	2.7	23.0	24.0	28.0	30.0
DH1260H-1R5M02	1.5	$\pm 20\%$	100	1000	2.4	3.0	22.0	24.0	32.0	34.0
DH1260H-2R2M	2.2	$\pm 20\%$	100	1000	3.1	3.8	20.0	22.0	26.0	27.0
DH1260H-3R3M	3.3	$\pm 20\%$	100	1000	5.0	6.0	16.0	17.0	25.0	26.0
DH1260H-4R7M	4.7	$\pm 20\%$	100	1000	7.5	9.0	14.0	15.0	19.0	20.0
DH1260H-5R6M	5.6	$\pm 20\%$	100	1000	9.0	11.0	13.0	14.0	17.0	18.0
DH1260H-6R8M	6.8	$\pm 20\%$	100	1000	10.5	13.0	12.0	13.0	16.0	17.0
DH1260H-8R2M	8.2	$\pm 20\%$	100	1000	15.0	20.0	9.0	10.0	15.0	16.0
DH1260H-100M	10	$\pm 20\%$	100	1000	15.0	20.0	9.0	10.0	13.0	14.0
DH1260H-100M01	10	$\pm 20\%$	100	1000	13.0	16.0	10.0	11.0	14.0	15.0
DH1260H-150M	15	$\pm 20\%$	100	1000	27.0	35.0	6.5	7.0	12.0	13.0
DH1260H-180M	18	$\pm 20\%$	100	1000	29.0	36.0	6.5	7.0	12.0	13.0
DH1260H-220M	22	$\pm 20\%$	100	1000	32.0	40.0	6.3	6.8	9.0	10.0
DH1260H-270M	27	$\pm 20\%$	100	1000	50.0	56.0	5.2	5.8	8.5	9.0
DH1260H-330M	33	$\pm 20\%$	100	1000	56.5	65.0	5.0	5.5	8.5	9.0
DH1260H-470M	47	$\pm 20\%$	100	1000	60.0	70.0	5.0	5.5	5.5	6.0
DH1260H-680M	68	$\pm 20\%$	100	1000	100.0	112.0	4.0	4.5	4.5	5.0
DH1260H-820M	82	$\pm 20\%$	100	1000	145.0	162.0	2.5	3.2	4.5	5.0
DH1260H-101M	100	$\pm 20\%$	100	1000	155.0	175.0	2.2	3.0	4.0	4.5

DH1260喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1260TJ-220M	22	$\pm 20\%$	100	22	32.5	40	6	8	13	14

DH1265系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1265H-R22MD	0.22	$\pm 20\%$	100	1000	0.55	0.75	40	45	60	75
DH1265H-R47MD	0.47	$\pm 20\%$	100	1000	0.75	1	38	42	50	60
DH1265H-R82MD	0.82	$\pm 20\%$	100	1000	1.6	2.1	26	28	33	35
DH1265H-1R0MD	1	$\pm 20\%$	100	1000	2.1	2.85	24	26	34	38
DH1265H-1R0M	1	$\pm 20\%$	100	1000	2.9	3.5	22.0	24.0	34.0	38.0
DH1265H-1R5MD	1.5	$\pm 20\%$	100	1000	2	2.8	24	26	28	30
DH1265H-1R5MD02	1.5	$\pm 20\%$	100	1000	2.4	3.2	23	25	32	34
DH1265H-2R2MD	2.2	$\pm 20\%$	100	1000	3.1	4.5	20	22	25	27
DH1265H-2R2M	2.2	$\pm 20\%$	100	1000	4.5	6	18.0	20.0	25.0	27.0
DH1265H-3R3M	3.3	$\pm 20\%$	100	1000	5	7.5	16	18	24	26
DH1265H-4R7M	4.7	$\pm 20\%$	100	1000	7.3	8.5	14.0	16.0	20.0	24.0
DH1265H-5R6M	5.6	$\pm 20\%$	100	1000	9.5	12	11	13	17	18
DH1265H-6R8M	6.8	$\pm 20\%$	100	1000	10.5	15	10	12	16	17
DH1265H-8R2M	8.2	$\pm 20\%$	100	1000	13	18	9.2	10.5	15	16
DH1265H-100M	10	$\pm 20\%$	100	1000	15	22	9	10	13	14
DH1265H-100M01	10	$\pm 20\%$	100	1000	13	18	9.2	10.5	13	15
DH1265H-150M	15	$\pm 20\%$	100	1000	27	35	7	8	12	13
DH1265H-150M01	15	$\pm 20\%$	100	1000	20	25	7.0	9.5	11.0	13.0
DH1265H-180M	18	$\pm 20\%$	100	1000	29	36	6.5	7.8	12	13
DH1265H-220M	22	$\pm 20\%$	100	1000	32	40	6	7.5	9	10
DH1265H-270M	27	$\pm 20\%$	100	1000	50	60	5.2	5.8	8	9

DH1265H-330M	33	±20%	100	1000	56.5	68	5	5.5	8	9
DH1265H-330M01	33	±20%	100	1000	43	52	5.0	5.5	8.0	8.5
DH1265H-470M	47	±20%	100	1000	60	70	4.5	5.5	6	8
DH1265H-680M	68	±20%	100	1000	100	115	3.5	4	4	5
DH1265H-820M	82	±20%	100	1000	145	165	3	3.5	4	5
DH1265H-101M	100	±20%	100	1000	155	175	2.7	3.2	4	4.5

DH1265喷漆系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1265TJ-1R0MD	1	$\pm 20\%$	100	1000	2	2.3	30.0	32.0	48.0	50.0
DH1265TJ-3R3M	3.3	$\pm 20\%$	100	1000	5.8	6	16.0	18.0	35.0	38.0
DH1265HY-4R7M	4.7	$\pm 20\%$	100	1000	7	10	14.0	16.0	18.0	19.0
DH1265HY-100M	10	$\pm 20\%$	100	1000	13	18	9.0	10.0	14.0	15.0
DH1265HY-150M	15	$\pm 20\%$	100	1000	21	31	7.0	8.0	12.0	13.0
DH1265HY-220M	22	$\pm 20\%$	100	1000	27	34	5.5	6.0	10.0	11.0
DH1265HY-330M	33	$\pm 20\%$	100	1000	42	55	5.0	5.5	7.0	7.5
DH1265HY-470M	47	$\pm 20\%$	100	1000	60	70	4.5	5.5	6.0	6.5
DH1265TJ-470M	47	$\pm 20\%$	100	1000	72	82	4.5	5.5	10.0	12.0
DH1265HY-750M	75	$\pm 20\%$	100	1000	70	82	4.5	5.0	4.0	4.5

DH1170系列

型号规格 Part NO.	标称感量 Inductance (μ H)	精度级别 Accuracy Grade	测试频率 Test Frequency (KHz)	测试电压 Test Voltage (mV)	直流电阻 Rdc (m Ω)		额定电流 Idc (A)		饱和电流 Isat (A)	
					Typ	Max	Max	Typ	Max	Typ
DH1770H-100M	10	$\pm 20\%$	100	1000	8.5	9.9	10.5	12.0	16.5	19.0
DH1770H-150M	15	$\pm 20\%$	100	1000	14	17	9.5	11.0	12.5	14.5
DH1770H-220M	22	$\pm 20\%$	100	1000	18	23	7.5	8.5	10.0	11.5
DH1770H-330M	33	$\pm 20\%$	100	1000	30.5	37	7.0	8.0	8.5	10.0
DH1770H-470M	47	$\pm 20\%$	100	1000	39	47	5.3	6.0	6.5	7.5
DH1770H-680M	68	$\pm 20\%$	100	1000	64	85	4.5	5.2	5.5	6.5